A Foundation for an Efficient Multi-Threaded Scheme System

Suresh Jagannathan Jim Philbin

NEC Research Institute

4 Independence Way

Princeton, NJ 08540

`<suresh | philbin>@research.nj.nec.com`

Abstract

We have built a parallel dialect of Scheme called STING that differs from its contemporaries in a number of important respects. STING is intended to be used as an operating system substrate for modern parallel programming languages.

The basic concurrency management objects in STING are first-class lightweight threads of control and virtual processors (VPs). Unlike high-level concurrency structures, STING threads and VPs are not encumbered by complex synchronization protocols. Threads and VPs are manipulated in the same way as any other Scheme structure.

STING separates thread policy decisions from thread implementation ones. Implementations of different parallel languages built on top of STING can define their own scheduling and migration policies without requiring modification to the runtime system or the provided interface. Process migration and scheduling can be customized by applications on a per-VP basis.

The semantics and implementation of threads minimizes the cost of thread creation, and puts a premium on storage locality. The storage management policies in STING lead to better cache and page utilization, and allows users to experiment with a variety of different execution regimes – from *fully delayed* to *completely eager* evaluation.

1 Introduction

The growing availability of general-purpose multiprocessors has led to increased interest in building efficient and expressive platforms for concurrent programming. Most efforts to incorporate concurrency into high-level symbolic programming languages such as Scheme[1, 23] or ML[18] involve the addition of special-purpose primitives (*e.g.*, parallel `let` operations[9], futures[11], events[24], etc.). These primitives are typically implemented using a dedicated runtime system sensitive to the particular semantics of these primitives.

Appears in the Proceedings of the 1992 ACM Symposium on Lisp and Functional Programming.

While reasonably efficient, these systems have nonetheless proven to be difficult to use as a substrate or foundation for a concurrent (symbolic) programming environment. This is because (a) the high-level semantics of the concurrency primitives they support lead to complex or inefficient implementations of other concurrency structures or paradigms; (b) the inaccessibility of the language's runtime structures make it cumbersome for applications to tailor the implementation based on their particular requirements; and, (c) the reliance on operating system services for process management and control found in many of these languages incurs high overhead in the presence of fine-grained, interactive, or realtime concurrency.

This paper describes an alternative approach to implementing concurrent symbolic programming languages. We have built a parallel dialect of Scheme called STING that differs from its contemporaries in a number of important respects. We outline the salient properties of the system below and elaborate upon these points throughout the paper:

Generality: The fundamental concurrency objects in STING are first-class lightweight threads of control and virtual processors (VPs). Unlike high-level concurrency structures, STING threads and VPs are not encumbered by complex synchronization protocols. Threads define a representation for a *process* or *task* and execute concurrently with other threads. Virtual processors are an abstraction of a physical computing device. VPs can be tailored to implement specialized process migration and scheduling protocols. Threads and VPs are manipulated in the same way as any other Scheme structure.

Efficiency: Because threads are fully integrated into the base language, and not provided as part of a library package[6], it is straightforward to optimize their implementation and use.

Thread operations are performed by a thread controller implemented as a procedure that allocates no storage. In addition, the semantics of threads and the design of the thread controller minimizes the cost of thread creation, and puts a premium on storage locality. Thus, the execution context for a newly terminated thread (*e.g.,* its stack and heap) is recycled and used immediately by other newly created threads, storage allocation is delayed until the thread actually executes, and different threads share the same stack and heap if data dependencies warrant. The storage management policies in STING lead to better cache and page utilization, and allows users to experiment with a variety of different execution regimes – from *fully delayed* to *completely eager* evaluation.

Programmability: Beyond providing mechanisms for managing concurrency, STING also handles exceptions across thread boundaries, preemption, non-blocking I/O, asynchronous storage management, and maintains extensive thread genealogy information. In addition, STING provides an infra-structure for implementing multiple address spaces, and long-lived persistent objects. As a result, we envision STING as an expressive operating system substrate upon which an advanced programming environment for parallel symbolic computing can be built.

Customizability: STING separates thread policy decisions from thread implementation ones. Although all threads conform to the same basic structure, implementations of different parallel languages built on top of STING may define their own scheduling, migration, and load-balancing policies without requiring modification to the thread controller or the provided interface. Process migration and scheduling concerns typically handled internally by a runtime library or an operating system in other languages can be customized by applications on a per-VP basis.

Unlike other systems that implement application dependent scheduling policies[28], STING does not incur a performance penalty for this flexibility; scheduling policy decisions are implemented entirely in STING and thus do not require a trap into a low-level system kernel.

The focus of this paper is on the design and implementation of the system. The implications of its design and its utility in expressing high-level paradigms for parallel symbolic computing are discussed in [13].

The remainder of the paper is structured as follows. Section 2 gives a brief description of the STING compiler and runtime system. Section 3 describes the structure of threads, and outlines the design of the thread manager. Section 4 provides a brief discussion the structure of virtual processors and support for process scheduling and thread migration. Section 5 presents details on thread creation, and runtime optimizations are discussed in Section 6. Section 7 gives an outline of the garbage collector. We present performance figures in Section 8. Section 9 gives comparison to related work, and Section 10 presents future directions.

2 The STING Abstract Machine

2.1 The Abstraction Hierarchy

The STING runtime environment is organized as a layer of abstractions. The lowest level consists of a physical machine containing a number of physical processors. Physical machines implement *virtual machines*; there may be many virtual machines executing on a single physical one. Each virtual machine may contain a number of *virtual processors.*

Each physical processor corresponds to a computing engine in a multiprocessor environment. Associated with every physical processor P is a physical policy manager (PPM) that handles scheduling decisions for the virtual processors that execute on P. A PPM will context switch among virtual processors because of preemption, or because it is explicitly requested to do so[1]. A physical processor may execute virtual processors associated with different virtual machines.

Virtual machines encapsulate a single address space managed exclusively by its virtual processors. Virtual machines may share global information (*e.g.,* libraries, file systems, etc.), and are responsible for mapping global objects (*i.e.,* objects resident in a global address space) into their local address space. Virtual machines also contain the root of a live object object graph (*i.e.,* the root environment) that is used to trace all live objects in its address space.

Virtual processors are responsible for executing and scheduling lightweight threads of control. In addition, they manage software interrupts (page faults, preemption, etc.). Different VPs within the same virtual machine may be closed over different scheduling policy managers. State transition operations on threads are implemented by a thread controller common to all VPs in the system.

All STING objects (including threads, VPs, and virtual machines) reside in a persistent memory. The memory is organized in terms of a collection of disjoint areas[4]. Objects are garbage collected within an area using a generational collector[17, 25]. An object can reference any other object found in its address space. Objects initially reside in short-lived thread-local areas. Objects that persist percolate upwards in the generation hierarchy. This functionality is completely transparent to the user.

2.2 Extensions to Scheme

The STING compiler is a modified version of Orbit[15]. The consing routine implemented by the compiler uses write-protected guard pages found at the top of every thread heap; an attempt to write onto this page triggers garbage collection. The garbage collector itself is significantly different from Orbit's because heaps and stacks are local to threads, and because inter-area references are supported.

[1] For example, a virtual processor may relinquish control of its physical processor if no threads are executing on it, and none are migratable from other VPs.

The target machine seen by the compiler also includes a dedicated thread register to hold a reference to the currently running thread object. Moreover, time critical operations such as those that save and restore registers on a context switch, allocate thread storage (*i.e.,* stacks and heaps), and execute test-and-set functions are provided as primops. Sequential Scheme programs will compile and execute without modification. STING implementations of futures, distributed data structures[5], and speculative concurrency operations also exist; Scheme programs can be freely augmented with the concurrency operations supported by any of these paradigms.

3 Threads

A STING thread defines a separate locus of control. A thread has a static and dynamic component (see Fig. 1). The static portion of a thread T contains state information indicating T's status (*e.g.,* delayed, scheduled, evaluating, etc.), a lock, the procedure P to be run, waiting threads blocked on the completion of T, P's dynamic and exception environment, and genealogy information indicating T's parent, children and sibling threads. Genealogy information is used for debugging and analysis. The value yielded by P's application is also stored in the thread upon completion.

Currently evaluating threads are associated with a *thread control block* (or TCB). The TCB contains information about the thread's dynamic context; a TCB is a generalized representation of a continuation and is closed over its own stack and heap. Besides storage objects, a TCB includes an associated lock, values of all live registers extant at the time the thread last performed a context switch, the current dynamic state of the running thread (*e.g.,* initialized, ready, evaluating, blocked, suspended, etc.), the next transition state for the thread, the VP on which the thread was last executing, thread priority, and time quantum. We introduce the operations allowable on threads and TCBs during the course of the paper.

The relationship between thread states and TCB states is given in Fig. 2. A thread in state *delayed* corresponds to a delayed or lazy object. A delayed thread will never be run unless the value of the thread's procedure is explicitly demanded. A *scheduled* thread is a thread known to a virtual processor, but which has not yet started evaluating. An *evaluating* thread is a thread which has been allocated a TCB and has started executing on some processor. Stolen threads are an important optimization of evaluating threads and are discussed in Section 6. A thread is *determined* if its associated procedure has been executed.

TCB states reflect the operations allowed on running threads. If running thread T has TCB T_b, the state field of T_b indicates one of the following:

initialized: The stack and heap associated with T_b have been initialized, but no code has yet been executed.

ready: T can execute on any available VP, but is currently not.



Figure 1: Organization of threads and TCBs.

running: T is currently executing on some VP.

blocked: T is currently blocked on some thread or condition.

suspended: T is suspended for some potentially infinite duration, and exists on a suspend queue of some VP.

terminated: T has finished executing.



Figure 2: Transition diagram for threads and TCBs.

Threads are first-class objects in STING and thus may be created dynamically, stored in objects, passed as arguments to (or returned as results from) procedures. Thread TCB's, on the other hand, are accessible only to thread controllers and policy managers. When a new thread is ready to run, a TCB is allocated for it; when a thread becomes determined, its TCB is available for use by the thread controller for threads created subsequently. TCBs never escape into user maintained data structures; they are manipulated exclusively by system-level procedures.

Since the register values recorded in the TCB of an evaluating thread T are used to establish thread context when T next executes, T's TCB represents the thread's continuation extant at the time T last performed a context switch. Since TCBs are not released to users, STING does not provide a user-level operation analogous to `call/cc` that operates over TCBs.

Users manipulate threads and TCBs via a set of procedures defined by the thread controller (TC); the TC implements state transition operations on threads. It is written entirely in STING with the exception of the primops outlined earlier. The core of the TC interface is given in an appendix.

A novel feature of the design permits threads to request state changes to other threads. In general, threads execute without need for requesting state changes to other threads. However, in certain important instances, such capability is desirable (*e.g.,* implementing speculative concurrency, or building common operating system services). The TCB `next-state` field provides this functionality. A state change to an evaluating thread T requested by other threads are record in T's `next-state` field (provided the requester has appropriate authority). Threads are only permitted to *request* a change to another thread; the actual realization of this change can only be done by the target thread when it next enters the thread controller.

The actual next state of a thread is determined by comparing its desired next state with its `next-state` field. This comparison is based on a simple total ordering:

`terminate` $\geq$ `suspend` $\geq$ `block` $\geq$ `ready` $\geq$ `running`

Because the ordering on state transitions is total and because only a thread can change its own state, the thread controller does not lock a TCB in order to determine the TCB's next state; if the next state requested is less than the current state, it can be ignored.

4 The Virtual Processor

A virtual processor is closed over a thread controller, a policy manager that defines the scheduling policy for the VP, a local "cache" of TCBs, and interrupt handlers that service page faults and preemption. Policy managers are closed over a set of queues holding threads and TCBs in various states of execution (*e.g.,* scheduled, ready, suspended, etc.).

The TCB cache is used by a VP to efficiently assign a dynamic context to a new thread. When a thread terminates, its TCB is reinitialized and kept in the VP TCB cache; a new thread created immediately thereafter on this VP is assigned this TCB. The overhead of thread/TCB assignment is reduced given the high likelihood that pieces of the terminated thread's TCB will still be in the VP's working set. All VPs within a virtual machine also share access to a global TCB pool (initialized at system startup) that is used if their cache is exhausted. TCBs are never created dynamically; the overhead in using TCBs is limited to their initialization and assignment to threads.

Virtual processors and virtual machines are first-class objects; part of the virtual machine state is a vector closed over the virtual processors defined by the machine. The system provides an interface to directly map virtual processors onto physical processors[22]. Thus, it is possible for applications to explicitly map computations onto specific processors as dictated by the parallel algorithm being implemented. For example, a process P known to communicate closely with Q (which is executing on VP V) should also run on a VP topologically near V[13]. As another example, first-class VPs and virtual machines make it possible to map arbitrary abstract topologies onto a concrete architectural surface[10].

The scheduling and migration routines executed by a virtual processor are customizable. Thus, different VPs may be closed over different scheduling regimes. The ability to customize policy managers has some significant implications. First, applications are free to optimize the scheduling of threads based on expected runtime dynamics of thread creation, longevity, and communication. Second, tasks found within a given application may be mapped onto virtual processors that implement the scheduling policy best suited for them. Different VPs can be dedicated to implement different schedulers; applications then map tasks onto VPs based on the scheduler required.

The policy manager implements a scheduling policy for the threads found on its VP, establishes a priority and quantum for the currently executing thread, and a load balancing policy that dictates how threads get mapped onto VPs. Load balancing in this context addresses two concerns: (1) how do threads initially get associated with a VP?, and (2) what are the criteria by which threads migrate across VPs?

The policy manager may implement any one of a number of scheduling policies (*e.g.,* FIFO, LIFO, realtime, interactive, round-robin, etc.). The overhead in accessing and updating thread queues can be customized as well; thus, a policy manager can classify threads as local (non-migratable) or global (migratable); local threads are stored on queues that involve no lock manipulation. There may be several ready queues holding threads with various priorities; long-lived threads may be stored on queues with lower priority than newly created threads. VPs may share access to global queues or can maintain their own local (private) images. The STING runtime environment provides a number of default policy managers; these managers (all written in STING) perform no dynamic storage allocation. Thus, users need not be aware of the policy manager to write STING programs. Applications that rely exclusively on these schedulers are guaranteed not to have threads trigger garbage collection on a state transition. We describe the semantics of some of the policy manager operations in the following sections.

5 Thread Creation and Execution

The implementation of the STING thread controller highlights a number of interesting issues. The state transition procedure is shown in Fig. 3. Note that operations on TCBs found in this procedure are not available to user applications.

The procedure takes two arguments – the desired next state for the current thread (*i.e.,* the thread which has entered the TC), and an argument field containing auxiliary information for threads that block or suspend. The procedure `get-tcb-next-state` returns the actual next state of the current TCB by comparing the value recorded in its `next-state` field with the `desired-next-state`.

Since the thread controller is written in STING, all synchronous calls to TC procedures are treated as ordinary procedure calls; thus, live registers used by the procedure running in the current thread are saved automatically in the thread's TCB. The procedure first attempts to acquire a new thread to execute from the ready queue of this VP. The policy manager procedure `pm-get-next-thread` is used for this purpose. Note that `pm-get-next-thread` enqueues the current thread's TCB if the TCB is in a ready state; this permits the thread to be rerun at some future point.

If the queue is empty, the root TCB of the current VP is invoked (via the call to `vp.root-tcb vp`). This procedure may (a) perform housekeeping operations, (b) simply reinvoke the state transition procedure, or (c) request the PPM to switch to a new VP.

If the queue is not empty, a new thread (or TCB) is returned. A new thread object is returned only if the thread is *not* evaluating. Such an object (call it T) is created and scheduled as a consequence of evaluating the expression:

`(fork-thread` *expr vp*`)`

This operation enqueues T on *vp*'s ready queue. It becomes eligible for evaluation when the TC removes it from the queue.

Once a thread begins evaluation, it is never directly stored in any queue maintained by a VP. Its TCB is stored

```
(define (state-transition desired-next-state arg)

  (receive (actual-next-state arg)
     (get-tcb-next-state desired-next-state arg)
    (set-new-state actual-next-state arg)
    (let ((vp (current-vp)))
      (let ((next
             (let ((next-thread (pm-get-next-thread vp)))
               (if (false? next-thread)
                   (vp.root-tcb vp)
                   next-thread))))
        (cond ((eq? next (current-tcb)))
              ((tcb? next)
               (set-tcb.state next tcb-state/running)
               (if (eq? desired-next-state tcb-state/dead)
                   (return-current-tcb-to-vp-pool vp))
               (set-vp.current-tcb vp next)
               (set-thread.vp (tcb.thread next) vp)
               (save-current-tcb-registers)
               (restore-tcb-and-registers next))
              ((thread? next)
               (if (thread-stolen? thread)
                   (state-transition desired-next-state arg)
                   (let ((tcb (setup-new-thread next-state next vp)))
                     (save-current-tcb-registers)
                     (start-new-tcb tcb start-new-thread))))))))))
```

Figure 3: Implementation of the state transition procedure. We use "." notation to express structure selection.

instead[2]. Thus, a TCB returned by `pm-get-next-thread` is always associated with an `evaluating` thread.

The outermost conditional in `state-transition` performs the actual context switch. If the current TCB happens to be the TCB returned by `pm-get-next-thread`, it is simply rerun – no extra register saves or restores need be performed (other than those needed to execute the call/return sequence to/from this procedure).

If the object returned by `pm-get-next-thread` is another (distinct) TCB, all live TCB registers of the current TCB are saved, and the continuation encapsulated in the TCB returned is restored. If the current TCB is dead (because it has terminated), it is recycled in the current VP's TCB pool. Because `restore-tcb-and-registers` is a primop, the compiler treats `save-current-tcb-registers` as if it were in a tail call position; thus, when the saved thread resumes execution (*i.e.,* assuming its TCB has not terminated), it simply returns from `state-transition`.

If the object returned is a thread, a TCB is allocated for it via the call `setup-new-thread` *provided* the thread has not been stolen (see Section 6). The current thread state is saved (via the call `save-current-tcb-registers`, and the new thread begin execution via the call to the primop `start-new-tcb`. This primop sets up a new continuation encapsulating the evaluation of `start-new-thread` and commences its evaluation using `tcb` as its dynamic context.

[2] The thread object associated with a non-terminated TCB is accessible via the `thread` slot found in that TCB.

Here again, the compiler treats the register save operation as if it were in a tail call position; thus, when the saved thread resumes execution it simply falls through the conditional and returns to the caller.

The code for `start-new-thread` is shown in Fig. 4.

A thread object with thunk E_t can begin evaluation once a TCB is allocated for it, and it becomes associated with a default error handler and appropriate cleanup code. Throws to `exit` (the default error handler) from E_t cause the thread stack to be unwound properly, thereby permitting resources such as locks held by the thread to be properly released. The exit code following the evaluation of E_t garbage collects the thread stack and heap, stores the value yielded by E_t as part of the thread state, wakes up all threads waiting for this value, reinitializes the TCB state and stores it back into the TCB pool (via the call to `re-initialize-tcb`), and finally makes a tail recursive call to the top-level transition procedure to choose a new thread to run. Because E_t is wrapped within a dynamic wind form, we guarantee that thread storage will be garbage collected and initialized even if a thread terminates abnormally.

Garbage collection must take place before the thread's waiters are awakened because objects that outlive the thread (including the object returned by the thread's thunk) found on its heap must be migrated to another live heap. Failure to do so would allow other threads to obtain references to the newly terminated thread's storage.

Preemption is disabled within the TC. Disabling preemp-

```
(define (start-new-thread)

  (let ((z (error-value "Thread has no value")))
    (unwind-protect (set z (catch exit
                             (set-tcb.exit-handler (current-tcb) exit)
                             ((thread.thunk (current-thread)))))
      (let ((thread (current-thread)))
        (set-tcb.state (current-tcb) tcb-state/terminated))
        (thread-gc thread)
        (set-thread.value thread z)
        (wakeup-waiters thread)
        (re-initialize-tcb (current-tcb))
        (record-current-thread-death)
        (state-transition tcb-state/dead '#f))
```

Figure 4: Starting a new thread.

tion guarantees that the TC will not be interrupted as a result of timer expiration. Other interrupts need not be disabled since TC-maintained data structures are not manipulated by VP interrupt handlers. Each VP has a separate area (implemented using small stacks and heaps) used by interrupts and the garbage collector for servicing any storage requirements they may have.

6 Stealing Threads

The STING implementation defers the allocation of storage for a thread until necessary. In many thread packages, the act of creating a thread involves not merely setting up the environment for the process to be forked, but also allocating and initializing storage. This approach lowers efficiency in two important respects: first, in the presence of fine-grained parallelism, the TC may spend more time creating and initializing threads than actually running them. Second, since stacks and process control blocks are immediately allocated upon thread creation, context switches among threads often cannot take advantage of cache and page locality.

Page locality in thread create operations is obviously important. Consider a virtual processor P executing thread T_1. Suppose T_1 spawns a new thread T_2. Under a fully eager thread creation strategy, storage for T_2 will be allocated from a new TCB. T_2's heap and stack will be mapped to a new set of physical pages in P's virtual machine. Thus, assume T_2 runs on P only after T_1 completes (*e.g.,* because there is no other free processor available or because T_1 is strict in the value yielded by applying T_2's thunk). Setting up T_2 now involves a fairly costly context switch. The working set valid when T_1 was executing is now possibly invalid; in particular, the contents of the data and instruction cache containing T_1's physical pages will probably need to be flushed when T_2 starts executing.

STING reduces the cost of eager thread allocation by deferring the acquisition of TCB stack and heap areas for a thread until it is actually about to be run. If an evaluating thread terminates, the next ready thread to be executed can *reuse* the TCB stack and heap space previously allocated to the terminated thread[16]. When a thread exits, its stack and heap storage are recycled for use by subsequent evaluating threads. Reusing thread storage increases locality since the contents of the processor cache and page mapping tables will contain pieces of the terminated process stack and heap. Just as significantly, delaying the allocation of thread storage minimizes the amount of housekeeping required; threads that are scheduled but which are never run (*e.g.,* because of unnecessary speculative parallelism) need never be allocated storage. Moreover, one processor can migrate such threads from another without inducing significant data movement since scheduled or delayed threads have small storage requirements.

The distinction between threads that are scheduled and those that are evaluating is used in STING to optimize the implementation of non-strict structures such as *futures*[11]; it's also used to throttle the unfolding of the process call tree in fine-grained parallel programs. In a naive implementation, a process that accesses a future (or which initiates a new process whose value it requires) blocks until the future becomes determined (or the newly instantiated process yields a value). This behavior is sub-optimal for the reasons described above – cache and page locality is compromised, bookkeeping information for context switching increases, and processor utilization is not increased since the original process must block until the new process completes.

STING implements the following optimization: a thunk t associated with a thread T that is in a *scheduled* or *delayed* state is applied using the dynamic context of a thread S if S demands T's value. The semantics of future/touch (or any similar producer/consumer protocol) is not violated. The rationale is straightforward: since T has not been allocated storage and has no dynamic state information associated with it, t can be treated as an ordinary procedure and evaluated using the TCB already allocated for S. In effect, S and T share the same dynamic storage. T's state is set to *stolen* as a consequence. A thread is stolen if its thunk executes using the TCB associated with another running thread.

Thus, in the STING implementation of futures[3], a process can run the code associated with an unevaluated future it touches within its own dynamic context – no TCB is allocated in this case and the accessing process does not block. A consumer blocks only when the producer has already started evaluating. The producer is already associated with a TCB in this case, and no opportunity for stealing presents itself.

Applying the closure of a stolen thread incurs some overheads not present in an ordinary procedure call. (Let T be a scheduled or delayed thread and let S be an evaluating thread that demands the value of T's thunk.) To steal S, the implementation performs the following actions:

1. The thread slot in S's TCB and the TCB slot in T is updated.
2. The dynamic state of S is stored in T; dynamic state information is used in case T raises an exception or throws to a catch point stored in S's TCB stack.
3. A catch point is wrapped around the application of S's thunk guaranteeing the stack and heap are in a consistent state if control throws out of the procedure being applied.
4. Thread related bookkeeping (*e.g.,* waking blocked threads, recording termination, etc.) is performed once S becomes determined.

These overheads are not significant, involving mostly stores to data structures (stacks, heaps, and records). No garbage collection is required in order to implement thread stealing.

Thread stealing is distinguished from the lazy task creation mechanism (also known as lazy futures) found in Mul-T[19] or Gambit[8], and load based-inlining as implemented in WorkCrews[26]. Whereas stealing permits the work needed to start a thread running to be deferred as long as possible, Mul-T lazy task creation is a technique intended to increase process granularity by permitting inlined tasks to be retroactively forked based on runtime conditions; load-based inlining in WorkCrews permits programs to notify free processors that a task is available for execution. Unlike either of these two approaches, thread stealing is not intended to be an *implementation* of a load balancing policy, although it does simplify the task of building such implementations; instead, the stealing operation prevents saturating the virtual machine with storage allocation requests, and improves cache and page performance of newly created threads. This is especially useful in result parallel programs in which processes typically exhibit significant data dependencies among one another. Neither lazy task creation nor load based inlining are intended to improve storage locality.

6.1 Synchronization

The primitive synchronization operation on threads is `thread-wait`. Given a thread T as its argument, this procedure first checks if T is determined. If T is under evaluation, the procedure stores the current thread in a queue, q, accessed via the `waiters` slot in T, and blocks the current thread[4]. When T becomes determined, all waiting threads on q are rescheduled using the procedure `wakeup-waiters`.

The *value* of a thread is the result yielded by applying its thunk. Threads can ask for the value of other threads using the procedure `thread-value` shown in Fig. 6.

If the argument thread T is determined, and its value is another thread, the procedure is applied recursively to this new thread; otherwise, the value is returned.

If T is either scheduled or delayed, T's state is set to stolen and it's thunk is evaluated using the current thread's TCB. `Run-stolen-thread` implements this behavior. Otherwise, the current thread blocks (via the `thread-wait` procedure); when it is rescheduled, its continuation makes a tail-recursive call to find T's value.

7 Garbage Collection

Each thread has a stack, a private heap and a public heap. Objects located in the stack are always private to the thread and are never collected. Objects in the private heap are accessible only to the thread that created them, while objects in the public heap are accessible to any thread in the system. A private object can become public by allowing a reference to it to escape the dynamic context of the thread in which it's found. Such objects are copied from the thread's private heap to its public heap. Both the private and public heaps use a generational style copying garbage collector. Any heap in the system can be collected independently of any other, but during the collection, objects in the heap are inaccessible to threads.

Our investigations and those of others[17, 25] indicate that most objects are created in the private heap nursery and die there. Because it is private, this heap can be collected by the thread at any time without affecting any other thread in the system. The root set for this collection is contained in the thread's stack and is thus usually quite small.

While any garbage collection is synchronous with respect to the thread doing the collecting, it is *asynchronous* with respect to other threads in the system. This type of asynchrony offers several benefits over completely synchronous garbage collectors[14]: (1) useful computation can proceed in the system even if some threads are garbage collecting, (2) the cost of garbage collection is not distributed evenly across all threads, but is charged proportionately to the amount of storage allocated by each thread; and (3) data locality is enhanced since objects are allocated in an area managed exclusively by the thread that creates them.

[3] Threads are a natural representation structure for futures. A future is created in sting using fork-thread; a touch on a future is equivalent to applying thread-value (see Section 6.1) on its thread argument.

[4] The policy manager does not store a blocked thread in any structure it maintains. Blocking is therefore tantamount to a context-switch in which the current thread is not recorded by the thread controller.