

# Chapter 5

## Network Layer: Control Plane

# Network layer: “control plane” roadmap

- introduction
- routing protocols
  - link state
  - distance vector
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- ~~SDN control plane~~
- Internet Control Message Protocol



- ~~network management, configuration~~
  - ~~SNMP~~
  - ~~NETCONF/YANG~~

# Network-layer functions

- **forwarding**: move packets from router's input to appropriate router output
- **routing**: determine route taken by packets from source to destination

*data plane*


*control plane*

## Two approaches to structuring network control plane:

- per-router control (traditional)
- logically centralized control (software defined networking)

# Per-router control plane

Individual routing algorithm components *in each and every router* interact in the control plane



# Network layer: “control plane” roadmap

- introduction
- routing protocols
  - link state
  - distance vector
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control Message Protocol




- network management, configuration
  - SNMP
  - NETCONF/YANG


# Routing protocols

**Routing protocol goal:** determine “good” paths (equivalently, routes), from sending hosts to receiving host, through network of routers

- **path:** sequence of routers packets traverse from given initial source host to final destination host
- **“good”:** least “cost”, “fastest”, “least congested”
- **routing:** a “top-10” networking challenge!



# Graph abstraction: link costs



$c_{a,b}$ : cost of *direct* link connecting  $a$  and  $b$

e.g.,  $c_{w,z} = 5$ ,  $c_{u,z} = \infty$


cost defined by network operator:  
could always be 1, or inversely related  
to bandwidth, or inversely related to  
congestion

graph:  $G = (N, E)$

$N$ : set of routers =  $\{ u, v, w, x, y, z \}$

$E$ : set of links =  $\{ (u,v), (u,x), (v,x), (v,w), (x,w), (x,y), (w,y), (w,z), (y,z) \}$

# Routing algorithm classification





# Network layer: “control plane” roadmap

- introduction
- routing protocols
  - link state
    - distance vector
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control Message Protocol



- network management, configuration
  - SNMP
  - NETCONF/YANG

# Dijkstra's link-state routing algorithm

- **centralized:** network topology, link costs known to *all* nodes
  - accomplished via “link state broadcast”
  - all nodes have same info
- computes least cost paths from one node (“source”) to all other nodes
  - gives *forwarding table* for that node
- **iterative:** after  $k$  iterations, know least cost path to  $k$  destinations

## notation

- $C_{x,y}$ : direct link cost from node  $x$  to  $y$ ;  $= \infty$  if not direct neighbors
- $D(v)$ : *current* estimate of cost of least-cost-path from source to destination  $v$
- $p(v)$ : predecessor node along path from source to  $v$
- $N'$ : set of nodes whose least-cost-path *definitively* known

# Dijkstra's link-state routing algorithm

1 *Initialization:*

2  $N' = \{u\}$  /\* compute least cost path from  $u$  to all other nodes \*/

3 for all nodes  $v$

4 if  $v$  adjacent to  $u$  /\*  $u$  initially knows direct-path-cost only to direct neighbors \*/

5 then  $D(v) = c_{u,v}$  /\* but may not be *minimum* cost! \*/

6 else  $D(v) = \infty$

7

8 *Loop*

9 find  $w$  not in  $N'$  such that  $D(w)$  is a minimum

10 add  $w$  to  $N'$

11 update  $D(v)$  for all  $v$  adjacent to  $w$  and not in  $N'$  :

12  $D(v) = \min ( D(v), D(w) + c_{w,v} )$


13 /\* new least-path-cost to  $v$  is either old least-cost-path to  $v$  or known

14 least-cost-path to  $w$  plus direct-cost from  $w$  to  $v$  \*/

15 *until all nodes in  $N'$*

# Dijkstra's algorithm: an example


Step	$N'$	$D(v), p(v)$	$D(w), p(w)$	$D(x), p(x)$	$D(y), p(y)$	$D(z), p(z)$
0	u	2, u	5, u	1, u	$\infty$	$\infty$
1	u, x	2, u	4, x		2, x	$\infty$
2	u, x, y	2, u	3, y			4, y
3	u, x, y, v		3, y			4, y
4	u, x, y, v, w					4, y
5	u, x, y, v, w, z					




Initialization (step 0): For all  $a$ : if  $a$  adjacent to then  $D(a) = c_{u,a}$

find  $a$  not in  $N'$  such that  $D(a)$  is a minimum  
 add  $a$  to  $N'$   
 update  $D(b)$  for all  $b$  adjacent to  $a$  and not in  $N'$  :  
 $D(b) = \min ( D(b), D(a) + c_{a,b} )$

# Dijkstra's algorithm: an example



resulting least-cost-path tree from u:



resulting forwarding table in u:


destination	outgoing link
v	(u,v)
x	(u,x)
y	(u,x)
w	(u,x)
z	(u,x)

route from  $u$  to  $v$  directly

route from  $u$  to all other destinations via  $x$

# Dijkstra's algorithm: another example

Step	$N'$	$D(v), p(v)$	$D(w), p(w)$	$D(x), p(x)$	$D(y), p(y)$	$D(z), p(z)$
0	u	7, u	3, u	5, u	$\infty$	$\infty$
1	uw	6, w		5, u	11, w	$\infty$
2	uwx	6, w			11, w	14, x
3	uwxv				10, v	14, x
4	uwxvy					12, y
5	uwxvyz					



## notes:

- construct least-cost-path tree by tracing predecessor nodes
- ties can exist (can be broken arbitrarily)

# Dijkstra's algorithm: discussion

**algorithm complexity:**  $n$  nodes


- each of  $n$  iteration: need to check all nodes,  $w$ , not in  $N$
- $n(n+1)/2$  comparisons:  $O(n^2)$  complexity
- more efficient implementations possible:  $O(n \log n)$

**message complexity:**


- each router must *broadcast* its link state information to other  $n$  routers
- efficient (and interesting!) broadcast algorithms:  $O(n)$  link crossings to disseminate a broadcast message from one source
- each router's message crosses  $O(n)$  links: overall message complexity:  $O(n^2)$

# Dijkstra's algorithm: oscillations possible


- when link costs depend on traffic volume, **route oscillations** possible
- sample scenario:
  - routing to destination a, traffic entering at d, c, e with rates 1, e (<1), 1
  - link costs are directional, and volume-dependent




initially



given these costs,  
find new routing....  
resulting in new costs



given these costs,  
find new routing....  
resulting in new costs



given these costs,  
find new routing....  
resulting in new costs



# Network layer: “control plane” roadmap

- introduction
- routing protocols
  - link state
  - **distance vector**
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control Message Protocol



- network management, configuration
  - SNMP
  - NETCONF/YANG

# Distance vector algorithm

Based on *Bellman-Ford* (BF) equation (dynamic programming):

Bellman-Ford equation

Let  $D_x(y)$ : cost of least-cost path from  $x$  to  $y$ .

Then:

$$D_x(y) = \min_v \{ c_{x,v} + D_v(y) \}$$


*min* taken over all neighbors  $v$  of  $x$

direct cost of link from  $x$  to  $v$

$v$ 's estimated least-cost-path cost to  $y$

# Bellman-Ford Example

Suppose that  $u$ 's neighboring nodes,  $x, v, w$ , know that for destination  $z$ :



Bellman-Ford equation says:

$$\begin{aligned} D_u(z) &= \min \{ c_{u,v} + D_v(z), \\ &\quad c_{u,x} + D_x(z), \\ &\quad c_{u,w} + D_w(z) \} \\ &= \min \{ 2 + 5, \\ &\quad 1 + 3, \\ &\quad 5 + 3 \} = 4 \end{aligned}$$

*node achieving minimum ( $x$ ) is next hop on estimated least-cost path to destination ( $z$ )*

# Distance vector algorithm

## key idea:


- from time-to-time, each node sends its own distance vector estimate to neighbors
- when  $x$  receives new DV estimate from any neighbor, it updates its own DV using B-F equation:

$$D_x(y) \leftarrow \min_v \{c_{x,v} + D_v(y)\} \text{ for each node } y \in N$$

- under minor, natural conditions, the estimate  $D_x(y)$  converge to the actual least cost  $d_x(y)$

# Distance vector algorithm:

each node:



**iterative, asynchronous:** each local iteration caused by:

- local link cost change
- DV update message from neighbor

**distributed, self-stopping:** each node notifies neighbors *only* when its DV changes

- neighbors then notify their neighbors – *only if necessary*
- no notification received, no actions taken!


# Distance vector: example



t=0

- All nodes have distance estimates to nearest neighbors (only)
- All nodes send their local distance vector to their neighbors

DV in a:	
$D_a(a)$	0
$D_a(b)$	8
$D_a(c)$	$\infty$
$D_a(d)$	1
$D_a(e)$	$\infty$
$D_a(f)$	$\infty$
$D_a(g)$	$\infty$
$D_a(h)$	$\infty$
$D_a(i)$	$\infty$



- A few asymmetries:
- missing link
  - larger cost


# Distance vector example: iteration



**t=1**

All nodes:

- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors




# Distance vector example: iteration



**t=1**

All nodes:

- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors






# Distance vector example: iteration



**t=1**

All nodes:

- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors




# Distance vector example: iteration



t=2

All nodes:

- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors




# Distance vector example: iteration



t=2

All nodes:

- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors




# Distance vector example: iteration



t=2

All nodes:

- receive distance vectors from neighbors
- compute their new local distance vector
- send their new local distance vector to neighbors



# Distance vector example: iteration

.... and so on

Let's next take a look at the iterative *computations* at nodes

# Distance vector example



**t=1**


- b receives DVs from a, c, e

DV in a:	
$D_a(a) = 0$	
$D_a(b) = 8$	
$D_a(c) = \infty$	
$D_a(d) = 1$	
$D_a(e) = \infty$	
$D_a(f) = \infty$	
$D_a(g) = \infty$	
$D_a(h) = \infty$	
$D_a(i) = \infty$	

DV in b:	
$D_b(a) = 8$	$D_b(f) = \infty$
$D_b(c) = 1$	$D_b(g) = \infty$
$D_b(d) = \infty$	$D_b(h) = \infty$
$D_b(e) = 1$	$D_b(i) = \infty$

DV in c:	
$D_c(a) = \infty$	
$D_c(b) = 1$	
$D_c(c) = 0$	
$D_c(d) = \infty$	
$D_c(e) = \infty$	
$D_c(f) = \infty$	
$D_c(g) = \infty$	
$D_c(h) = \infty$	
$D_c(i) = \infty$	

DV in e:	
$D_e(a) = \infty$	
$D_e(b) = 1$	
$D_e(c) = \infty$	
$D_e(d) = 1$	
$D_e(e) = 0$	
$D_e(f) = 1$	
$D_e(g) = \infty$	
$D_e(h) = 1$	
$D_e(i) = \infty$	




# Distance vector example



t=1

- b receives DVs from a, c, e, computes:

DV in a:	
$D_a(a) = 0$	
$D_a(b) = 8$	
$D_a(c) = \infty$	
$D_a(d) = 1$	
$D_a(e) = \infty$	
$D_a(f) = \infty$	
$D_a(g) = \infty$	
$D_a(h) = \infty$	
$D_a(i) = \infty$	



DV in b:	
$D_b(a) = 8$	$D_b(f) = \infty$
$D_b(c) = 1$	$D_b(g) = \infty$
$D_b(d) = \infty$	$D_b(h) = \infty$
$D_b(e) = 1$	$D_b(i) = \infty$

DV in c:	
$D_c(a) = \infty$	
$D_c(b) = 1$	
$D_c(c) = 0$	
$D_c(d) = \infty$	
$D_c(e) = \infty$	
$D_c(f) = \infty$	
$D_c(g) = \infty$	
$D_c(h) = \infty$	
$D_c(i) = \infty$	

DV in e:	
$D_e(a) = \infty$	
$D_e(b) = 1$	
$D_e(c) = \infty$	
$D_e(d) = 1$	
$D_e(e) = 0$	
$D_e(f) = 1$	
$D_e(g) = \infty$	
$D_e(h) = 1$	
$D_e(i) = \infty$	

$$D_b(a) = \min\{c_{b,a} + D_a(a), c_{b,c} + D_c(a), c_{b,e} + D_e(a)\} = \min\{8, \infty, \infty\} = 8$$

$$D_b(c) = \min\{c_{b,a} + D_a(c), c_{b,c} + D_c(c), c_{b,e} + D_e(c)\} = \min\{\infty, 1, \infty\} = 1$$

$$D_b(d) = \min\{c_{b,a} + D_a(d), c_{b,c} + D_c(d), c_{b,e} + D_e(d)\} = \min\{9, 2, \infty\} = 2$$

$$D_b(e) = \min\{c_{b,a} + D_a(e), c_{b,c} + D_c(e), c_{b,e} + D_e(e)\} = \min\{\infty, \infty, 1\} = 1$$

$$D_b(f) = \min\{c_{b,a} + D_a(f), c_{b,c} + D_c(f), c_{b,e} + D_e(f)\} = \min\{\infty, \infty, 2\} = 2$$

$$D_b(g) = \min\{c_{b,a} + D_a(g), c_{b,c} + D_c(g), c_{b,e} + D_e(g)\} = \min\{\infty, \infty, \infty\} = \infty$$

$$D_b(h) = \min\{c_{b,a} + D_a(h), c_{b,c} + D_c(h), c_{b,e} + D_e(h)\} = \min\{\infty, \infty, 2\} = 2$$

$$D_b(i) = \min\{c_{b,a} + D_a(i), c_{b,c} + D_c(i), c_{b,e} + D_e(i)\} = \min\{\infty, \infty, \infty\} = \infty$$

DV in b:	
$D_b(a) = 8$	$D_b(f) = 2$
$D_b(c) = 1$	$D_b(g) = \infty$
$D_b(d) = 2$	$D_b(h) = 2$
$D_b(e) = 1$	$D_b(i) = \infty$

# Distance vector example



**t=1**


- c receives DVs from b

DV in a:	
$D_a(a) = 0$	
$D_a(b) = 8$	
$D_a(c) = \infty$	
$D_a(d) = 1$	
$D_a(e) = \infty$	
$D_a(f) = \infty$	
$D_a(g) = \infty$	
$D_a(h) = \infty$	
$D_a(i) = \infty$	

DV in b:	
$D_b(a) = 8$	$D_b(f) = \infty$
$D_b(c) = 1$	$D_b(g) = \infty$
$D_b(d) = \infty$	$D_b(h) = \infty$
$D_b(e) = 1$	$D_b(i) = \infty$

DV in c:	
$D_c(a) = \infty$	
$D_c(b) = 1$	
$D_c(c) = 0$	
$D_c(d) = \infty$	
$D_c(e) = \infty$	
$D_c(f) = \infty$	
$D_c(g) = \infty$	
$D_c(h) = \infty$	
$D_c(i) = \infty$	

DV in e:	
$D_e(a) = \infty$	
$D_e(b) = 1$	
$D_e(c) = \infty$	
$D_e(d) = 1$	
$D_e(e) = 0$	
$D_e(f) = 1$	
$D_e(g) = \infty$	
$D_e(h) = 1$	
$D_e(i) = \infty$	





# Distance vector example



t=1

- c receives DVs from b computes:

$$D_c(a) = \min\{c_{c,b} + D_b(a)\} = 1 + 8 = 9$$

$$D_c(b) = \min\{c_{c,b} + D_b(b)\} = 1 + 0 = 1$$

$$D_c(d) = \min\{c_{c,b} + D_b(d)\} = 1 + \infty = \infty$$


$$D_c(e) = \min\{c_{c,b} + D_b(e)\} = 1 + 1 = 2$$

$$D_c(f) = \min\{c_{c,b} + D_b(f)\} = 1 + \infty = \infty$$

$$D_c(g) = \min\{c_{c,b} + D_b(g)\} = 1 + \infty = \infty$$

$$D_c(h) = \min\{c_{c,b} + D_b(h)\} = 1 + \infty = \infty$$

$$D_c(i) = \min\{c_{c,b} + D_b(i)\} = 1 + \infty = \infty$$



DV in b:	
$D_b(a) = 8$	$D_b(f) = \infty$
$D_b(c) = 1$	$D_b(g) = \infty$
$D_b(d) = \infty$	$D_b(h) = \infty$
$D_b(e) = 1$	$D_b(i) = \infty$

DV in c:
$D_c(a) = \infty$
$D_c(b) = 1$
$D_c(c) = 0$
$D_c(d) = \infty$
$D_c(e) = \infty$
$D_c(f) = \infty$
$D_c(g) = \infty$
$D_c(h) = \infty$
$D_c(i) = \infty$

DV in c:
$D_c(a) = 9$
$D_c(b) = 1$
$D_c(c) = 0$
$D_c(d) = 2$
$D_c(e) = \infty$
$D_c(f) = \infty$
$D_c(g) = \infty$
$D_c(h) = \infty$
$D_c(i) = \infty$

\* Check out the online interactive exercises for more examples:  
[http://gaia.cs.umass.edu/kurose\\_ross/interactive/](http://gaia.cs.umass.edu/kurose_ross/interactive/)

# Distance vector example



**t=1**

- e receives DVs from b, d, f, h


DV in d:	
$D_c(a) = 1$	
$D_c(b) = \infty$	
$D_c(c) = \infty$	
$D_c(d) = 0$	
$D_c(e) = 1$	
$D_c(f) = \infty$	
$D_c(g) = 1$	
$D_c(h) = \infty$	
$D_c(i) = \infty$	

DV in h:	
$D_c(a) = \infty$	
$D_c(b) = \infty$	
$D_c(c) = \infty$	
$D_c(d) = \infty$	
$D_c(e) = 1$	
$D_c(f) = \infty$	
$D_c(g) = 1$	
$D_c(h) = 0$	
$D_c(i) = 1$	

DV in b:	
$D_b(a) = 8$	$D_b(f) = \infty$
$D_b(c) = 1$	$D_b(g) = \infty$
$D_b(d) = \infty$	$D_b(h) = \infty$
$D_b(e) = 1$	$D_b(i) = \infty$

DV in e:	
$D_e(a) = \infty$	
$D_e(b) = 1$	
$D_e(c) = \infty$	
$D_e(d) = 1$	
$D_e(e) = 0$	
$D_e(f) = 1$	
$D_e(g) = \infty$	
$D_e(h) = 1$	
$D_e(i) = \infty$	






DV in f:	
$D_c(a) = \infty$	
$D_c(b) = \infty$	
$D_c(c) = \infty$	
$D_c(d) = \infty$	
$D_c(e) = 1$	
$D_c(f) = 0$	
$D_c(g) = \infty$	
$D_c(h) = \infty$	
$D_c(i) = 1$	




n

# Distance vector: state information diffusion

Iterative communication, computation steps diffuses information through network:


-  t=0 c's state at t=0 is at c only
-  t=1 c's state at t=0 has propagated to b, and may influence distance vector computations up to **1** hop away, i.e., at b
-  t=2 c's state at t=0 may now influence distance vector computations up to **2** hops away, i.e., at b and now at a, e as well
-  t=3 c's state at t=0 may influence distance vector computations up to **3** hops away, i.e., at b,a,e and now at c,f,h as well
-  t=4 c's state at t=0 may influence distance vector computations up to **4** hops away, i.e., at b,a,e, c, f, h and now at g,i as well



# Distance vector: link cost changes

## link cost changes:

- node detects local link cost change
- updates routing info, recalculates local DV
- if DV changes, notify neighbors



“good news travels fast”

$t_0$ :  $y$  detects link-cost change, updates its DV, informs its neighbors.


$t_1$ :  $z$  receives update from  $y$ , updates its table, computes new least cost to  $x$ , sends its neighbors its DV.

$t_2$ :  $y$  receives  $z$ 's update, updates its distance table.  $y$ 's least costs do *not* change, so  $y$  does *not* send a message to  $z$ .

# Distance vector: link cost changes

## link cost changes:

- node detects local link cost change
- “bad news travels slow” – count-to-infinity problem:
  - y sees direct link to x has new cost 60, but z has said it has a path at cost of 5. So y computes “my new cost to x will be 6, via z); notifies z of new cost of 6 to x.
  - z learns that path to x via y has new cost 6, so z computes “my new cost to x will be 7 via y), notifies y of new cost of 7 to x.
  - y learns that path to x via z has new cost 7, so y computes “my new cost to x will be 8 via y), notifies z of new cost of 8 to x.
  - z learns that path to x via y has new cost 8, so z computes “my new cost to x will be 9 via y), notifies y of new cost of 9 to x.
  - ...
- see text for solutions. *Distributed algorithms are tricky!*



# Distance Vector: link cost increases

$$D_y(x) = \min\{c(y,x) + D_x(x), c(y,z) + D_z(x)\}$$

$$= \min\{60+0, 1+5\} = 6$$

**node y table**

		cost to		
		x	y	z
from	y	4	0	1
	x	0	4	5
	z	5	1	0

**when y detects**

		cost to		
		x	y	z
from	y	6	0	1
	x			
	z			

**node z table**

		cost to		
		x	y	z
from	z	5	1	0
	y	4	0	1
	x	0	4	5


		cost to		
		x	y	z
from	z	7	1	0
	y			
	x			

**node x table**

		cost to		
		x	y	z
from	x	0	4	5
	y	4	0	1
	z	5	1	0

$$D_z(x) = \min\{c(z,y) + D_y(x), c(z,x) + D_x(x)\}$$

$$= \min\{1+6, 50+0\} = 7$$



# Distance Vector: link cost increases

## node y table

		cost to		
		x	y	z
from	y	4	0	1
	x	0	4	5
	z	5	1	0

## node z table

		cost to		
		x	y	z
from	z	5	1	0
	y	4	0	1
	x	0	4	5

## node x table

		cost to		
		x	y	z
from	x	0	4	5
	y	4	0	1
	z	5	1	0

## when y detects

		cost to		
		x	y	z
from	y	6	0	1
	x			
	z			

$$D_y(x) = \min\{c(y,x) + D_x(x), c(y,z) + D_z(x)\}$$

$$= \min\{60+0, 1+7\} = 8$$


		cost to		
		x	y	z
from	z	7	1	0
	y			
	x			

		cost to		
		x	y	z
from	y	8	0	1
	x			
	z			

		cost to		
		x	y	z
from	z	9	1	0
	y			
	x			

$$D_z(x) = \min\{c(z,y) + D_y(x), c(z,x) + D_x(x)\}$$

$$= \min\{1+8, 50+0\} = 9$$



# Comparison of LS and DV algorithms

## message complexity

LS:  $n$  routers,  $O(n^2)$  messages sent

DV: exchange between neighbors;  
convergence time varies

## speed of convergence

LS:  $O(n^2)$  algorithm,  $O(n^2)$  messages

- may have oscillations

DV: convergence time varies

- may have routing loops
- count-to-infinity problem

robustness: what happens if router malfunctions, or is compromised?

LS:

- router can advertise incorrect *link* cost
- each router computes only its *own* table

DV:

- DV router can advertise incorrect *path* cost (“I have a *really* low cost path to everywhere”): black-holing
- each router’s table used by others: error propagate thru network



# Network layer: “control plane” roadmap

- introduction
- routing protocols
- **intra-ISP routing: OSPF**
- routing among ISPs: BGP
- SDN control plane
- Internet Control Message Protocol



- ~~network management, configuration~~
  - ~~SNMP~~
  - ~~NETCONF/YANG~~

# Making routing scalable

our routing study thus far - idealized

- all routers identical
- network “flat”

... not true in practice

**scale:** billions of destinations:

- can't store all destinations in routing tables!
- routing table exchange would swamp links!

**administrative autonomy:**

- Internet: a network of networks
- each network admin may want to control routing in its own network

# Internet approach to scalable routing

aggregate routers into regions known as “autonomous systems” (AS) (a.k.a. “domains”)

## intra-AS (aka “intra-domain”):

routing among *within same AS* (“network”)


- all routers in AS must run same intra-domain protocol
- routers in different AS can run different intra-domain routing protocols
- **gateway router**: at “edge” of its own AS, has link(s) to router(s) in other AS'es

## inter-AS (aka “inter-domain”):

routing *among* AS'es

- gateways perform inter-domain routing (as well as intra-domain routing)

# Interconnected ASes



forwarding table configured by intra- and inter-AS routing algorithms

- intra-AS routing determine entries for destinations within AS
- inter-AS & intra-AS determine entries for external destinations


# Inter-AS routing: a role in intradomain forwarding

- suppose router in AS1 receives datagram destined outside of AS1:

- ? router should forward packet to gateway router in AS1, but which one?

**AS1 inter-domain routing must:**

1. learn which destinations reachable through AS2, which through AS3
2. propagate this reachability info to all routers in AS1



# Inter-AS routing: routing within an AS

most common intra-AS routing protocols:

- **RIP: Routing Information Protocol** [RFC 1723]
  - classic DV: DVs exchanged every 30 secs
  - no longer widely used
- **EIGRP: Enhanced Interior Gateway Routing Protocol**
  - DV based
  - formerly Cisco-proprietary for decades (became open in 2013 [RFC 7868])
- **OSPF: Open Shortest Path First** [RFC 2328]
  - link-state routing
  - IS-IS protocol (ISO standard, not RFC standard) essentially same as OSPF

# OSPF (Open Shortest Path First) routing

- “open”: publicly available
- classic link-state
  - each router floods OSPF link-state advertisements (directly over IP rather than using TCP/UDP) to all other routers in entire AS
  - multiple link costs metrics possible: bandwidth, delay
  - each router has full topology, uses Dijkstra’s algorithm to compute forwarding table
- *security*: all OSPF messages authenticated (to prevent malicious intrusion)

# Hierarchical OSPF


- **two-level hierarchy:** local area, backbone.
  - link-state advertisements flooded only in area, or backbone
  - each node has detailed area topology; only knows direction to reach other destinations

## area border routers:

“summarize” distances to destinations in own area, advertise in backbone


## local routers:

- flood LS in area only
- compute routing within area
- forward packets to outside via area border router






# Hierarchical OSPF Example




1. Run OSPF within area 1

# Hierarchical OSPF Example




# Hierarchical OSPF Example




1. Run OSPF within area 3

# Hierarchical OSPF Example



**1. Run OSPF within area 1, 2, 3**

# Hierarchical OSPF Example



**1. Run OSPF within area 1, 2, 3**

**3. Router K in Area 3 updates its table based on R<sub>6</sub>**

# Network layer: “control plane” roadmap

- introduction
- routing protocols
- intra-ISP routing: OSPF
- **routing among ISPs: BGP**
- ~~SDN control plane~~
- Internet Control Message Protocol




- ~~network management, configuration~~
  - ~~SNMP~~
  - ~~NETCONF/YANG~~

# Internet inter-AS routing: BGP



- **BGP (Border Gateway Protocol):** *the* de facto inter-domain routing protocol
  - “glue that holds the Internet together”
- allows subnet to advertise its existence, and the destinations it can reach, to rest of Internet: *“I am here, here is who I can reach, and how”*
- BGP provides each AS a means to:
  - **eBGP:** obtain subnet reachability information from neighboring ASes
  - **iBGP:** propagate reachability information to all AS-internal routers.
  - determine “good” routes to other networks based on reachability information and *policy*

# eBGP, iBGP connections





# BGP routers exchange messages




**While connection is ALIVE,  
exchange route UPDATE  
messages**

# BGP message types

- Exchanged over TCP connection among two BGP routers (“peers”)
- BGP message types:
  - OPEN: opens TCP connection to peer and authenticates sender
  - UPDATE: advertises new path (or withdraws old)
  - KEEPALIVE: keeps connection alive in absence of UPDATES; also ACKs OPEN request
  - NOTIFICATION: reports errors in previous msg; also used to close connection

# BGP basics

- **BGP session:** two BGP routers (“peers”) exchange BGP messages over semi-permanent TCP connection:
  - advertising *paths* to different destination network prefixes (BGP is a “path vector” protocol)
- when AS3 gateway 3a advertises *path AS3,X* to AS2 gateway 2c:
  - AS3 *promises* to AS2 it will forward datagrams towards X




# AS Numbers (ASNs)

- ❖ ASNs are 4-byte #s now; denote units of routing policy
  - ASN once was 2-byte before 2007.
- ❖ AS 4200000000 ~ 4294967294 (94,967,295 ASes) are reserved for private usage (not visible in the Internet).

- **Level 3 Communications, Inc: 1**
- **MIT: 3**
- **UCB: 25**
- **USC: 47**
- **UCLA: 52**
- **JPL: 127**
  
- **AT&T: 2386, 2686, 7018, 5074, 5075, ...**
- **UUNET: 701, 702, 284, 12199, ...**
- **Sprint: 1239, 1240, 6211, 6242, ...**

**Source:** <http://www.bgplookingglass.com/list-of-autonomous-system-numbers>

# ASes are well connected! (AS Graphs)




**The subgraph showing all ASes that have more than 100 neighbors in full graph of 11,158 nodes. July 6, 2001. Point of view: AT&T route-server**

# Path attributes and BGP routes


- BGP advertised route: prefix + attributes
  - prefix: destination being advertised
  - two important attributes:
    - **AS-PATH**: list of ASes through which prefix advertisement has passed
    - **NEXT-HOP**: indicates specific internal-AS router to next-hop AS
- **policy-based routing**:
  - gateway receiving route advertisement uses *import policy* to accept/decline path (e.g., never route through AS Y).
  - AS policy also determines whether to *advertise* path to other neighboring ASes

# BGP path advertisement



- AS2 router 2c receives path advertisement **AS3, X** (via eBGP) from AS3 router 3a
- based on AS2 policy, AS2 router 2c accepts path **AS3, X**, propagates (via iBGP) to all AS2 routers
- based on AS2 policy, AS2 router 2a advertises (via eBGP) path **AS2, AS3, X** to AS1 router 1c

# BGP path advertisement (more)




gateway router may learn about **multiple** paths to destination:

- AS1 gateway router 1c learns path **AS2,AS3,X** from 2a
- AS1 gateway router 1c learns path **AS3,X** from 3a
- based on *policy*, AS1 gateway router 1c chooses path **AS3,X** and advertises path within AS1 via iBGP




# BGP path advertisement



- recall: 1a, 1b, 1d learn via iBGP from 1c: “path to X goes through 1c”
- at 1d: OSPF intra-domain routing: to get to 1c, use interface 1
- at 1d: to get to X, use interface 1

# BGP path advertisement



# Why different Intra-, Inter-AS routing ?

## policy:

- inter-AS: admin wants control over how its traffic routed, who routes through its network
- intra-AS: single admin, so policy less of an issue


## scale:

- hierarchical routing saves table size, reduced update traffic

## performance:


- intra-AS: can focus on performance
- inter-AS: policy dominates over performance

# Hot potato routing



- 2d learns (via iBGP) it can route to X via 2a or 2c
- **hot potato routing**: choose local gateway that has least *intra-domain* cost (e.g., 2d chooses 2a, even though more AS hops to X): don't worry about inter-domain cost!


# BGP: achieving policy via advertisements



ISP only wants to route traffic to/from its customer networks (does not want to carry transit traffic between other ISPs – a typical “real world” policy)

- A advertises path Aw to B and to C
- B *chooses not to advertise* BAw to C!
  - B gets no “revenue” for routing CBAw, since none of C, A, w are B’s customers
  - C does *not* learn about CBAw path
- C will route CAw (not using B) to get to w

# BGP: achieving policy via advertisements (more)




ISP only wants to route traffic to/from its customer networks (does not want to carry transit traffic between other ISPs – a typical “real world” policy)

- A,B,C are **provider networks**
- x,w,y are **customer** (of provider networks)
- x is **dual-homed**: attached to two networks
- **policy to enforce**: x does not want to route from B to C via x
  - .. so x will not advertise to B a route to C

# BGP route selection

- router may learn about more than one route to destination AS, selects route based on:
  1. local preference value attribute: policy decision
  2. shortest AS-PATH
  3. closest NEXT-HOP router: hot potato routing
  4. additional criteria

# Another example: How AS path is formed





# Network layer: “control plane” roadmap

- introduction
- routing protocols
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- ~~SDN control plane~~
- **Internet Control Message Protocol**




- ~~network management, configuration~~
  - ~~SNMP~~
  - ~~NETCONF/YANG~~

# ICMP: internet control message protocol

- used by hosts and routers to communicate network-level information
  - error reporting: unreachable host, network, port, protocol
  - echo request/reply (used by ping)
- network-layer “above” IP:
  - ICMP messages carried in IP datagrams
- *ICMP message*: type, code plus first 8 bytes of IP datagram causing error

<u>Type</u>	<u>Code</u>	<u>description</u>
0	0	echo reply (ping)
3	0	dest. network unreachable
3	1	dest host unreachable
3	2	dest protocol unreachable
3	3	dest port unreachable
3	6	dest network unknown
3	7	dest host unknown
4	0	source quench (congestion control - not used)
8	0	echo request (ping)
9	0	route advertisement
10	0	router discovery
11	0	TTL expired
12	0	bad IP header

# Traceroute and ICMP



- source sends sets of UDP segments to destination
    - 1<sup>st</sup> set has TTL =1, 2<sup>nd</sup> set has TTL=2, etc.
  - datagram in  $n$ th set arrives to  $n$ th router:
    - router discards datagram and sends source ICMP message (type 11, code 0)
    - ICMP message possibly includes name of router & IP address
  - when ICMP message arrives at source: record RTTs
- stopping criteria:
- UDP segment eventually arrives at destination host
  - destination returns ICMP “port unreachable” message (type 3, code 3)
  - source stops

# Network layer: Summary

*we've learned a lot!*

- approaches to network control plane
  - per-router control (traditional)
  - logically centralized control (software defined networking)
- traditional routing algorithms
  - implementation in Internet: OSPF , BGP
- Internet Control Message Protocol

*next stop: link layer!*